

During warehousing or transport, cardboard and paperboard products should be stored in accordance with the following conditions, under risk of the complaint not being accepted:

1. The product should be stored in well-ventilated premises, in the temperature in the range from 5 to 30 °C, and humidity in the range from 30 to 70%. It is forbidden to cause sudden changes of temperature and humidity in the warehousing areas.
2. The product should not be placed directly in the floor but should be stored on pallets or platforms with dry and clean surface.
3. The product should be protected against precipitation. Any water condensation caused by humidity inside the packed pallet should be prevented. The pallet cannot have any contact with water or snow, in particular when it is moved or when the floor near the pallet is cleaned.
4. The product cannot be exposed to direct sunlight.
5. The product should be protected against dust and other types of dirt.
6. The product should be protected against sources of heat and sudden or frequent changes of atmospheric conditions, i.e. frequent opening of the door, direct impact of air from ventilation or heating system.
7. It should be ensured that the product is properly moved depending on the size of production in accordance with the FIFO rule (first in/first out).
8. The product delivered to the warehouse should be kept in the same condition as when it was delivered from the printing house without removing any protections until its use.
9. Stacking of pallets should be avoided because it can cause damage of the products located on the lowest pallet.
10. While removing protections from the pallet (straps, foil), sharp equipment (for example a knife) should be used with care so that the packed products are not damaged.
11. All identification documents of the pallet, i.e. labels, hangers etc. should be stored until all products from the pallet are used.